



BTP-T150 Ticket Printer

Items		BTP-T150
Print	Print method	Direct thermal
	Resolution	203DPI
	Print width	Max.56 mm (2.2")
	Print speed	Max.100mm/s
	Memory	64KB RAM 1MB/2MB/4MB Flash
	Black mark detection	Photo sensor
	Driver	Windows Driver (WIN98/ NT/2000/XP/2003)
	Communicate interface	Serial /USB/Parellel
Barcode	Barcode	UPC-A, UPC-E, EAN 13, EAN 8 CODE 39, CODE 93, ITF, CODABAR, CODE128
	Fonts	Standard ASCII: 12 × 24 Compressed ASCII: 9 × 17 Big fonts: 24 × 24
		When use big fonts, user can select one of following: Simple Chinese (GB2312), Simple Chinese (GB18030), Traditional Chinese, Korean, Japanese.
	Graphics	Character modification
		Underline, emphasize, rotate (0°, 90°, 180°, 270°) reverse, enlarge (1~6 times)
	Graphics	BMP bitmap can be downloaded to RAM or FLASH
Paper	Paper type	Continuous paper/Marked paper
	Paper thickness	0.08~0.25mm
	Paper roll	Paper roll external
Power supply	Input	AC 220V ± 5%, 50/60Hz
	Output	DC 24V, 2.5A
Environment	Operating	5~45℃, 20%~90% RH (Non-condensed)
	Storage	-40~60℃, 20%~93% RH (Non-condensed)
Physics spec.	Dimensions (W × H × D)	185mm × 153 mm × 239mm
	Weight	3.5kg