

# smart 81D

**Print Now.**  
Print More.



## New Trusted Identity Begins

Experience next-generation performance with the SMART-81D, the industry's fastest retransfer card printer. Powered by our exclusive Rapid Retransfer Printing (RRP) technology, the SMART-81D goes from power-on to "Fastest First Card Out" in just seconds—eliminating long warm-up times common in older retransfer printers.

Delivering ultra-sharp, high-resolution images with rich, deep colors and true edge-to-edge (full-bleed) coverage, the SMART-81D is ideal for high-security credentials, bank cards, and technology cards that demand premium print quality.

RRP technology from IDP offers power-on and Fastest First Card Out. The SMART-81D produces higher quality, sharper-looking images than traditional card printers. It is the perfect choice for demanding applications that require deep dark colors with infinity-edge (full-bleed) graphics on blank or technology cards.

The input card hopper holds up to 200 cards and physical security features allow you to secure your printer, its supplies, and ejected cards in instant bank card issuance or high-security applications.

## Features

- Fastest First Card Out – Industry-leading speed
- High-Capacity Input – 200-card hopper for uninterrupted high-volume printing
- Infinity Edge Printing – Stunning full-bleed image quality with rich, vibrant detail
- Dust-Resistant Design – Smart airflow system reduces defects caused by dust
- Option Banking Security – Designed to meet advanced security and compliance needs
- Durable & Modern – Engineered for performance with a sleek, robust design



## Issuance

SMART IDesigner ensures accurate card issuance and data management with your SMART series of printers. This application offers simple design tools to allow the user to create a truly customized card within minutes. SMART IDesigner offers advanced user tools such as database connections, camera and signature scanners, plug-in support, as well as smart card reading and encoding.

- Design and print (Image, Photo, and Text)
- 1D & 2D Barcode printing
- Auto portrait (Auto face detection, adjustment of size & position)
- Printing of sequential numbers
- Card design templates
- Plug-in for supporting external devices (Sign pad, Camera, Scanner)
- Convenient card issuance and data management
- Magnetic stripe (MS), contact & contactless smart card encoding by using a plug-in program

## Security

The SMART series printers come with highly effective and tested physical and electronic security features.

- PASSWORD verification with administrator and user authentications
- PC AUTHENTICATION locks the SMART printer to a specific PC to render it useless if stolen
- DATA ENCRYPTION over USB and SSL (secure socket layer) over Ethernet
- PHYSICAL LOCKS are standard on the SMART-70 and an optional feature on the SMART-51 Series
- Ethernet - SNMPv3

## Networking

The SMART series offers "single-wire" printing and encoding.

- The SMART Ethernet module can not only print over your network, but can also be configured to encode a magnetic stripe, contact IC chips, and contactless smart cards over your network
- The SMART Ethernet module can be configured to accept "open card protocol" print commands for direct printing without a driver

## Printing

Print Type	Dye-Sublimation / Resin Thermal Retransfer
Print Area	Dual-Sided/Over-the-Edge
Resolution	300dpi/600dpi

## Print Speed

Monochrome	Max. 25 sec./card (144 cards/hour)
YMCKK	Max. 43 sec./card (84 cards/hour)

## System

Display	2 Line Graphic LCD Indicator / 4 Buttons
Supported Platforms	Windows 10/11, Mac OS, Linux
Communication	USB, Ethernet (Option)
Power Supply	100-240V~ 50/60Hz 2.5A
Temperature/Humidity	15~35°C/35~70%

## Certifications

CB CE FCC IC

## Card

Card Feeding	Automatic
Card Size	ISO CR80 (54mm x 86mm/2.12" x 3.38")
Card Thickness	0.76mm (30mil) ~ 1.6mm (64mil)
Card Type	PVC, PET, Composite PVC

## Capacity

Input Hopper	200 Cards
Output Hopper	100 Cards

## Dimensions

Millimeter (WxDxH)	460 x 224 x 310
Inch (WxDxH)	18.1 x 8.8 x 12.2

## Weight

Kg/lbs	11.4 / 25.13
--------	--------------

## Encoding Options

Magnetic	ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo)
Contact	ISO 7816 (ID-1)
Contactless	ISO 14443 (Type A/ B), ISO 18092(NFC), MIFARE, DESFIRE
Security	Physical & Electronic Locking System

## Consumables



Color Ribbons

YMCK

Full Color Ribbon with Resin Black

500 Cards/Roll

YMCKK

Full Color Ribbon with Resin Black & Resin Black for Back Side

500 Cards/Roll



Retransfer Film

Retransfer Film

500 Cards/Roll



Ribbon & Film Package

YMCK & Retransfer Film

Full Color Ribbon with Resin Black & Retransfer Film

500 Cards/Roll



\*Optional SMART-81L Lamination Add-On for SMART-81 Series Card Printers

## IDP Americas, Inc.

1485 South County Trail - Unit 306,  
East Greenwich, RI 02818  
TEL +1.401.400.7111  
FAX +1.401.667.7445  
E-MAIL sales@idpamericas.com

## IDP Corp., Ltd.

#601, 50, Digital-ro 33-gil,  
Guro-gu, Seoul, Korea, 08377  
TEL +82.2.6099.3700  
FAX +82.2.6099.3717  
E-MAIL sales@idp-corp.com

653637  
653538  
653539  
653540  
653708  
653547  
653378  
653379  
653431  
653629  
900849  
653630  
653631

**SMART-81D 300dpi**  
**Magnetic Stripe Enc. Standard**  
**Contact SmartCard Enc.**  
**Contactless SmartCard Enc.**  
**Contact IC (ISO 7816 ID-1) & Contactless**  
**YMCK & Retransfer Film Pack**  
**YMCKK (no film included)**  
**YMCFK (no film included)**  
**Retransfer INTM Film (no ink included)**  
**Clear 1mil Laminate Film**  
**Globe Flags Hologram 1 mil Film**  
**Celestial Hologram 1 mil Film**  
**Clear IC Chip, 1mil Film**