


TDW108

PREMIUM FLAT HEAD WAX



PRODUCT DESCRIPTION

This grade is a premium wax ribbon, designed to give outstanding print performance on plain and coated papers. This wax is recommended for applications where price is the main factor. It offers a black, crisp and bold print making it an ideal product for standard printing applications that require a low level of durability to the printed image. The low level of printhead energy required to transfer the ink makes this wax a drop-in replacement product for other waxes available in the market and will offer a good performance on all types of flat head technology printers. With print performance at speeds of up to 10" per second, at low printhead energy, this wax maintains excellent quality on low cost substrates. This wax also has the additional advantage of being ISEGA approved for use when the printed image comes into contact with dry, moist and fatty foodstuffs.

RECOMMENDED SUBSTRATES

Vellum, uncoated, matt coated, semi-gloss, tag board

PERFORMANCE PROPERTIES

PRINT SENSITIVITY

9

HEAT RESISTANCE

4

ABRASION RESISTANCE

4

SOLVENT RESISTANCE

3

LABEL ADAPTABILITY

7

LOW

MEDIUM

HIGH

TYPICAL APPLICATIONS



LOGISTICS



RETAIL



GENERAL



INVENTORY



PRODUCT ID



SHIPPING



NUMBER PLATES



TDW108

PREMIUM FLAT HEAD WAX

PERFORMANCE CHARACTERISTICS

- Ideal for coated and uncoated papers
- Excellent print quality at high speeds (up to 10"/second)
- Excellent print definition for clean, durable and dense barcodes
- Drop-in product to competitors wax ribbons
- Very low printhead energy requirements
- ISEGA certification
- Available from stock for all popular printers
- Very competitively priced

TDW108

RIBBON SPECIFICATIONS	
DESCRIPTION	TECHNICAL
BASE FILM CARRIER	4.5 Micron Polyester
TOTAL RIBBON THICKNESS	7.3 Microns +/- 0.02
INK TYPE	Wax (flat head technology)
COLOUR	Black
INK MELTING POINT	65°C
DENSITY	1.9

RIBBON STORAGE CONDITIONS	
DESCRIPTION	TECHNICAL
TEMPERATURE	5°C to 35°C (41F to 95F)
HUMIDITY	10% to 85% relative humidity
LIGHT	Avoid direct sunlight

CERTIFICATIONS AND APPROVALS

DESCRIPTION	TECHNICAL
ISO 9001:2015 & ISO 14001:2015	All ribbons have been manufactured to these international quality standard
RoHs/WEEE	EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment
HEAVY METALS	94/62/EC & 2011/65/EU
TSCA/CP 65	The ribbon does not contain any of the substances on this list
AMES TEST	The ribbon is not mutagenic, does not cause DNA modifications
EC DIRECTIVES	1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health
FOOD CONTACT	1935/2004/EC
REACH/SVHC	Does not contain any of the SVHCs listed - 1907 / 2006/EC
DISPOSAL	To be disposed of as mixed industrial waste

This information is the best available on the above ribbon grade. These results should, however, only be regarded as a general guide to material properties and is not a guarantee.

ISEGA

FDA

